

DATA SHEET

BM - BC
GF - CP
DT - AI
AE

DUCTS FOR
AIR CON-
DITIONING
SYSTEMS

CANALIZ-
ZAZIONI PER
IMPIANTI DI
CONDIZIO-
NAMENTO




PRODUCT DESCRIPTION

Material: VO self-extinguishing PVC
Operating temperature: -20° +60° C



DIMENSIONS



TYPE	L	H
BC 60	60	45
BC 80	80	60
BC 120	110	75

BM - BC

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
BC 60	Raceway base with lid of 2 ml. bars	1 ml	24 pcs
BC 80	Raceway base with lid of 2 ml. bars	1 ml	16 pcs
BC 120	Raceway base with lid of 2 ml. bars	1 ml	8 pcs

GF

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
GF 60	Flexible joint	1 ml	6 pcs
GF 80	Flexible joint	1 ml	4 pcs

CP

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
CP 60	Flat curve	1 ml	10 pcs
CP 80	Flat curve	1 ml	8 pcs
CP 120	Flat curve	1 ml	6 pcs

DT

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
DT 80	T diversion	1 ml	4 pcs
DT 120	T diversion	1 ml	2 pcs

AI

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
AI 60	90° external angle	1 ml	8 pcs
AI 80	90° external angle	1 ml	6 pcs
AI 120	90° external angle	1 ml	4 pcs

AE

CODE	DESCRIPTION	BEARING CAPACITY	PACK SIZE
AE 60	90° external angle	1 ml	12 pcs
AE 80	90° external angle	1 ml	9 pcs
AE 120	90° external angle	1 ml	6 pcs

Rodigas S.r.l.
via Giacomelli, 10
35010 Limena
(PADOVA) ITALY
Tel +39 049 8840056
Fax +39 049 8840060
info@rodigas.it
www.rodigas.it